



## CRST19F

尺寸(Dimensions):21X10X12mm

## 特点 Features

- 1,线圈功耗低 Low coil power consumption.
- 2,体积小,重量轻 Small size,Light weight .
- 3,可直接焊接在印刷细路板中 PC board mounting.
- 4,用于家用电器,自动化系统,电子设备,仪器仪表,通讯装置,遥控装置等, Suitable for household electrical appliances,automation system,electronic equipment,instrument,meter,telecommunication facilities and remote control facilities.

## 订货信息 Ordering information

CRST19F--2C--DC12V-L

1 2 3 4

- 1,型号 Part number: CRST19F 2,触点形式 Contact arrangement 2C:2C
- 3,线圈额定电压 Coil Rated voltage(V):DC:3,5,6,9,12,24
- 4,线圈功耗 Coil power consumption:无 Nil 0.2W(标准 Standard);L:0.15W(高灵敏度 High sensitivity)

## 触点数据 Contact data

触点形式 Contact Arrangement	2C(2Z)(DPDT)	
触点材料 Contact Material	AgNi, Ag	
触点负载(阻性) Contact Rating(Resistive)	3A/28VDC,2A30VDC;0.5A,1A/125VAC,24VDC	
最大切换功率 Max.Switching Power	84W 125VA	
最大切换电压 Max.Switching Voltage	30VDC 220VAC 最大切换电流 Max.Switching Current:3A	
触点阻性或压降 Contact Resistance or Voltage Drop	≤50mΩ	
寿命 Operation Life	电气 Electrical	10 <sup>5</sup>
	机械 Mechanical	10 <sup>7</sup>

## 线圈参数 Coil Parameter

线圈电压 Coil voltage (VDC)		线圈电阻 Coil Resistance Ω ±10%	吸合电压 VDC(最大) Pick up Voltage VDC(Max) (额定电压的 75%) (75% of rated voltage)	释放电压 VDC Release voltage VDC(Min) (额定电压的 10%) (10% of rated voltage)	线圈功耗 Coil power consumption (W)	动作时间 Operate Time (mS)	释放时间 Release Time (mS)
额定 Rated	最大 Max						
5	6.5	166.7	3.50	0.5	0.15	≤6	≤5
6	7.8	240.0	4.20	0.6			
12	15.6	960.0	8.40	1.2			
24	31.2	3840.0	18.0	2.4			
5	6.5	125.0	3.50	0.5	0.20	≤6	≤5
6	7.8	405.0	4.20	0.6			
12	15.6	720.0	8.40	1.2			
24	31.2	2880	18.0	2.4			

注意:1,使用的线圈电压低于线圈额定电压时将会损害继电器的工作.

2,吸合,释放电压仅供检测用,不是设计的使用指标.


Caution:1,The use of any coil voltage less than the rated coil voltage will compromise the operation of the relay.

2,Pick up and release voltage are for test purposes only and are not be used as design criteria.


## 技术特性 Operation condition

绝缘电阻 Insulation Resistance	最少 1000MΩ min(at 500V)
介质耐压 Dielectric Strength	
断开触点间 Between Contacts	50Hz 500V
触点与线圈间 Between Contacts and Coil	50Hz 1000V
耐冲击 Shock Resistance	500m/s <sup>2</sup> 11ms
抗振性 Vibration Resistance	10~70Hz 双振幅 Double amplitude 1.5mm
引出端强度 Terminals Strength	5N
可焊性 Solderability	235±2℃ 3±0.5s℃
环境温度 Ambient Temperature	-30~70℃
相当湿度 Relative Humidity	85%(at 40℃)
质(重)量 Mass	5g


## 外形尺寸 Dimensions(mm/Inch)



外形尺寸图  
Dimensions



安装尺寸图 (底视图)  
Mounting (Bottom view)



接线图 (底视图)  
Wiring diagram (Bottom view)

注: 1) 尺寸以毫米为单位。  
NOTES Dimensions are in millimeters.  
2) 给出的等量英寸值仅供参考。  
Inch equivalents are given for general information only

## 参考数据 Reference Data

